

When Things go Wrong

Error Handling in SQL Server

Erland Sommarskog
SQL Server MVP

SQLSat Kyiv Team



Eugene Polonichko



Alesya Zhuk



Yevhen Nedashkivskyi



Oksana Tkach



Mykola Pobyivovk



Oksana Borysenko

Our Awesome Sponsors



Microsoft



intapp™



DB-BEST
TECHNOLOGIES

eleks®



devart
Database Interaction Solutions

DATAART

infopulse

<epam>

DIGITALUKRAINE



доставка
крафтового
пива

Sponsor Sessions Starts at 13:10

- Don't miss them, they might be providing some interesting and valuable information!

	Room A	Room B	Room C
13:00 - 13:20	DevArt	Microsoft	Eleks
13:20 - 13:50	DB Best	Intapp	DataArt

Session will begin very soon :)

Please complete the evaluation form from your pocket after the session. Your feedback will help us to improve future conferences and speakers will appreciate your feedback!

Enjoy the conference!

A photograph of a forest path. The path is made of dirt and stones, leading through tall green grass and ferns. In the background, there are many trees, including tall pine trees and some deciduous trees with bare branches. The lighting is natural, suggesting daytime.

Erland Sommarskog

Independent consultant based in Stockholm

SQL Server MVP since 2001

<http://www.sommarskog.se>

esquel@sommarskog.se

Agenda

Focus: How to handle unexpected errors.

- What action does SQL Server take in case of error?
- SET XACT_ABORT ON.
- TRY-CATCH.
- How to write CATCH blocks.
- Client-Side Error Handling.
- How to handle nested procedures and transactions.
- A quick look at natively compiled stored procedures.

What Actions Can SQL Server Take?

Internal SQL Server Errors

Default (when XACT_ABORT is ON)

Many user errors willy-nilly

1. Close the connection.

Appeared first in SQL 2012

2. Abort the batch and roll back transaction.

Compilation errors at run-time

3. Abort the batch without rolling back.

4. Abort the scope and continue in caller.


5. Roll back statement and continue on next.

Many user errors willy-nilly

What Actions Can SQL Server Take?

SET XACT_ABORT ON changes this:

1. Close the connection.
2. Abort the batch and roll back transaction.
- ~~3. Abort the batch without rolling back.~~
- ~~4. Abort the scope and continue.~~
- ~~5. Roll back statement and continue next.~~
6. Ignores XACT_ABORT ON.



RAISERROR,
Error 266,
syntax errors.

Attention Signals

Tells SQL Server to abandon execution.

Occurs with the client-side error "Timeout expired".

Also generated by the red button in SSMS.

Statement is always rolled back.

Transaction rolled back **only** if
XACT_ABORT is **on**.

Recommendation

Always have this statement on top of your stored procedures:

```
SET XACT_ABORT, NOCOUNT ON
```

More consistent error behaviour.

Reduces the risk for orphaned transactions.

Takeaway So Far

You cannot rely on that you will be able to continue execution on error.

You cannot rely on that execution will be aborted on error.

Therefore:

- Keep it simple.
- Use TRY-CATCH.

TRY-CATCH

Error in TRY block transfers execution to CATCH block.

Transaction may be *doomed* – must be rolled back. [TryCatch.sql](#)

Errors that roll back transaction =>
Dooming errors.

Perfectly reasonable for deadlock, resource errors. Less so for conversion errors.

Transaction always doomed with
XACT_ABORT ON.

Not All Errors Are Catchable

Internal errors that close the connection.

Compilation errors in the scope they occur – can be caught in outer scope.

Various odd errors cannot be caught, more common with linked servers or CLR.

Attention signals.

CATCH Block Recipe

Important principle: Since this is code that is in **every** procedure it should be short and non-intrusive. Two lines, that's all:

1. Roll back any open transaction.
2. Re-raise the error.

Roll Back Open Transactions

`IF @@trancount > 0 ROLLBACK TRANSACTION`
Always have this line.

You may not have a `BEGIN TRANSACTION` today – but that could change later.

You may call a procedure which begins a transaction but fails to commit/roll back.

What about caller's transaction? We'll talk about that later.

Re-raising the Error

Custom procedure

- Only choice on SQL 2005/2008.
- Want to log error or other custom behaviour.
- Avoids the semicolon trap.

;THROW

- Simple. :-)
- All error messages are preserved as-is.
- Makes sure that execution is aborted.

Client-side Error Handling

All calls to SQL Server must be error-checked and in case of error, the client must always submit

```
IF @@trancount > 0 ROLLBACK TRANSACTION
```

(Or rollback through its own trans object.)

Don't rely on the SQL code having XACT_ABORT ON. Each component should do its job.

Make sure you get all result sets!

"Nested" Transactions

BEGIN TRANSACTION

-- Transaction starts.

BEGIN TRANSACTION

-- Increments @@trancount.

COMMIT TRANSACTION

-- Decrements @@trancount. That's all.

COMMIT TRANSACTION

-- @@trancount = 0 => Transaction commits.

ROLLBACK TRANSACTION -- Rolls back it all.

Nested Procedures

What if outer procedure starts a transaction...

...and calls an inner procedure that also starts a transaction?

Should inner CATCH handler roll back all?

Ideally, no.

In practice YES, because:

- There is no better way in SQL Server.
- The inner procedure has failed to fulfil its contract.

Savepoints to the Rescue?

```
BEGIN TRANSACTION MyTran  
-- First part  
SAVE TRANSACTION Throw  
-- Second part  
ROLLBACK TRANSACTION Throw
```

This rolls back only Second Part, but transaction is alive and First Part can still be committed.

Useful?

Savepoints are Useless

Cannot roll back to savepoint when transaction is doomed.

Always doomed with `XACT_ABORT ON`.

And even with `OFF`, rollback is only possible for some errors.

Not supported in distributed transactions.

Natively Compiled Stored Procedures

```
CREATE PROCEDURE hekaton_sp  
WITH NATIVE_COMPILATION, SCHEMABINDING AS  
BEGIN ATOMIC WITH  
    (TRANSACTION ISOLATION LEVEL=SNAPSHOT,  
     LANGUAGE='us_english')  
    -- SQL code here.  
END
```


Natively Compiled Procedures, cont'd

Procedure == Transaction.

Only need TRY-CATCH for expected errors.

BEGIN/COMMIT/ROLLBACK TRAN not permitted.

A nested SP call defines an implicit savepoint.

An uncaught error aborts the procedure and rolls back to the savepoint.

Transactions doomed for a reason – only concurrency and resource errors.

In short: how error handling should be!

Summary – Aims and Means

Always communicate unexpected errors – don't lure users to think they see correct data.

- Re-raise the error!
- Get all result sets!

Always abort execution on unexpected errors – don't persist incorrect data.

- SET XACT_ABORT ON
- IF @@trancount > 0 ROLLBACK TRAN
- Re-raise the error!

Summary – Aims and Means

Prevent orphaned transactions.

- SET XACT_ABORT ON
- IF @@trancount > 0 ROLLBACK TRANSACTION
- Also in client code!!

Don't lose the original error message – without it troubleshooting is very difficult.

- Keep things simple.
- Watch out for the semicolon trap!

That's All Folks!


Erland Sommarskog
esquel@sommarskog.se

Slides and scripts on
<http://www.sommarskog.se/present>

Three parts and three appendixes? Start here:

http://www.sommarskog.se/error_handling/Part1.html

Our Awesome Sponsors



Microsoft



intapp™



DB-BEST
TECHNOLOGIES

eleks®



devart
Database Interaction Solutions

DATAART

infopulse

<epam>

DIGITALUKRAINE



доставка
крафтового
пива